M



# United States Patent and Trademark Office

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO. FIRST NAMED INVENTOR ATTORNEY DOCKET NO. CONFIRMATION NO. FILING DATE 10/612,125 07/02/2003 Andrew Weeks Kueny 946959-600013 3892 41498 7590 06/28/2006 **EXAMINER** RUDOLPH J. BUCHEL JR., LAW OFFICE OF MISLEH, JUSTIN P P. O. BOX 702526 ART UNIT PAPER NUMBER DALLAS, TX 75370-2526 2622

DATE MAILED: 06/28/2006

Please find below and/or attached an Office communication concerning this application or proceeding.

		Application No.	Applicant(s)	
Office Action Summary		10/612,125	KUENY, ANDREW WEEKS	
		Examiner	Art Unit	
		Justin P. Misleh	2622	
The MAILING DATE of this communication appears on the cover sheet with the correspondence address				
Period fo		//0.055.50.50.50.50.50.50.50.50.50.50.50.5		
WHIC - Exter after - If NO - Failu Any	ORTENED STATUTORY PERIOD FOR REPLY CHEVER IS LONGER, FROM THE MAILING DANSIONS of time may be available under the provisions of 37 CFR 1.13 SIX (6) MONTHS from the mailing date of this communication. It is to reply is specified above, the maximum statutory period or reply within the set or extended period for reply will, by statute, reply received by the Office later than three months after the mailing ed patent term adjustment. See 37 CFR 1.704(b).	ATE OF THIS COMMUNICATION 36(a). In no event, however, may a reply be tin will apply and will expire SIX (6) MONTHS from the cause the application to become ABANDONE	N. nely filed the mailing date of this communication. D (35 U.S.C. § 133).	
Status				
1)⊠	Responsive to communication(s) filed on 12 A	<u>oril 2006</u> .		
2a)⊠	This action is <b>FINAL</b> . 2b) This action is non-final.			
3)	Since this application is in condition for allowance except for formal matters, prosecution as to the merits is			
closed in accordance with the practice under Ex parte Quayle, 1935 C.D. 11, 453 O.G. 213.				
Dispositi	ion of Claims			
5)□ 6)⊠ 7)⊠	<ul> <li>4)  Claim(s) 1 - 50 is/are pending in the application.</li> <li>4a) Of the above claim(s) is/are withdrawn from consideration.</li> <li>5)  Claim(s) is/are allowed.</li> <li>6)  Claim(s) 1 - 4, 14 - 16, 23 - 29, and 33 - 50 is/are rejected.</li> <li>7)  Claim(s) 5 - 13, 17 - 22, and 30 - 32 is/are objected to.</li> <li>8)  Claim(s) are subject to restriction and/or election requirement.</li> </ul>			
Applicati	ion Papers			
<ul> <li>9) ☐ The specification is objected to by the Examiner.</li> <li>10) ☐ The drawing(s) filed on 7-2-03 is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.  Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).  Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).</li> <li>11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.</li> </ul>				
Priority (	under 35 U.S.C. § 119			
<ul> <li>12) Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).</li> <li>a) All b) Some * c) None of:</li> <li>1. Certified copies of the priority documents have been received.</li> <li>2. Certified copies of the priority documents have been received in Application No</li> <li>3. Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).</li> <li>* See the attached detailed Office action for a list of the certified copies not received.</li> </ul>				
Attachmen	• •	A) 🖂 Intention Summer	(PTO 413)	
2) Notice 3) Information	ce of References Cited (PTO-892) ce of Draftsperson's Patent Drawing Review (PTO-948) mation Disclosure Statement(s) (PTO-1449 or PTO/SB/08) er No(s)/Mail Date	4) Interview Summary Paper No(s)/Mail Do 5) Notice of Informal F 6) Other:		

Art Unit: 2622

**;** `

## **DETAILED ACTION**

# Response to Arguments

1. Applicant's arguments filed April 12, 2006 have been fully considered but they are not persuasive.

With respect to <u>all</u> of the independent claims (e.g., 1, 25, 28, 33, and 41), Applicant mainly makes the following arguments:

Applicant initially argues, "it is not immediately clear from the body of the rejection how the examiner incorporates wither of the operational modes for kinetic spectroscopy embodiment disclosed by West with the multiline spectroscopy embodiment."

Applicant additionally argues, "it is respectfully asserted that West neither teaches nor suggests the present invention because West does not teach or suggest combining charge that was integrated in the first and second regions in the N registers, but instead teaches binning charge from one region in the first row pixels in the other region, and further because West does not teach or suggest two dependently controlled regions but instead the operation of West's device relies on two independently controlled regions that are separated by asymmetrical split."

With respect to <u>only</u> independent Claim 33, Applicant additionally makes the following argument:

Applicant argues, "nowhere does West teach or suggest 'shifting charge from the at least some pixels of the first region and second dependently controlled region of the N linear pixel arrays along a linear path into said dark dependently controlled region of the N linear pixel arrays of the imaging sensor,' as recited in claim 33."

Art Unit: 2622

2. First of all, as clearly set forth in the rejection of Claim 1 (for exemplary purposes), the Examiner mainly relied upon West's teachings in column 4 (lines 29-67), column 5 (lines 1-3, 10-27, and 56-62), and column 6 (lines 1-11) and implicitly relied upon West's figures 3 and 4. The Examiner further relied upon West's column 5 (lines 34-40) for additional support. All of the portions of West that the Examiner cited, including figures 3 and 4, are clearly directed towards multiline spectroscopy, with the exception of the any of the citations extracted from column 5 (lines 41-62). The Examiner only relied upon certain kinetic spectroscopy teachings of West (i.e., portions extracted from column 5, lines 41-62) for the purposes of additionally supporting the fact that West *bins* pixel charges from a plurality of rows into a single row, a major feature of previously presented and currently amended exemplary Claim 1. Of course, it goes without saying that the Examiner's reliance upon the multiline spectroscopy embodiment of West is also true for each of the independent claims (e.g., 25, 28, 33, and 41). In contrast to

Page 3

3. Second of all, amended Claim 1 now recites, *inter alia*, "combining charge from a first dependently controlled region of the N linear pixel arrays of the imaging sensor" and "combining charge from a second dependently controlled region of the N linear pixel arrays of the imaging sensor"; however, Claim 1 does not recite how or, more importantly, where the charges from the respective first and second regions are combined. Neither does Claim 1 recite the section or portion of the region or imaging sensor each of the first region and second region are

Applicant's allegation, the Examiner did not combine multiple embodiments from West. Rather,

the Examiner looked at the specific teachings of the reference in its entirety to obtain an

appreciation of what the reference fairly teaches to with one skilled in the art.

dependently controlled with respect to. Accordingly, the claim language is written broadly enough such that the West provides the necessary teachings.

In the Office Action, the Examiner relied upon item 401 of figure 4 to be the claimed first region and also relied upon item 402 of figure 4 to be the claimed second region. As pointed out by Applicant and as agreed upon by the Examiner, charges from the rows in the first region (401) are *binned* into a single row corresponding to item 406 of figure 4 and charges from the rows in the second region (402) are also *binned* into the single row (406), of course at separate times. Also, as indicated by Applicant and agreed upon by the Examiner, the section of the imaging sensor where charges are collected during multiline spectroscopy (section 301 of figure 4) and the section where charges are *binned* (section 302 of figure 4) are independently controlled.

However, the Examiner submits that all of the rows in each respective section (301 and 302) of West are dependently controlled with respect to that section. In other words, the rows in the first region (401) cannot be shifted without synchronously shifting the rows in the second region (402). Accordingly, the rows in section (302) must operate synchronously with each other. Since the claim language does not specify where the charges are combined and or with what the respective regions are dependently controlled with respect to, the Examiner's analysis sufficiently demonstrates how West provides the necessary teachings to anticipate the cited portion of newly amended Claim 1. Of course, the Examiner's analysis is equally applicable to all the independent claims (e.g., 25, 28, 33, and 41).

4. Finally, with respect to Claim 33, the cited portion of the claim language is written broadly enough such only a portion of either of the first region or the second region I required to be shifted into a dark region. The Examiner notes West satisfies this requirement because figure

Application/Control Number: 10/612,125 Page 5

Art Unit: 2622

4 (also see column 4, lines 49 - 59) clearly shows that the charges from the second region (402) must be shifted through a dark region (405a) to be binned in the single row (406).

## Specification

5. The disclosure is objected to because it contains an embedded hyperlink and/or other form of browser-executable code (see pages 3 and 4). Applicant is required to delete the embedded hyperlink and/or other form of browser-executable code. See MPEP § 608.01.

# Claim Objections

- 6. Claim 28 is objected to because of the following informalities: lack of clarity and precision.
- 7. Claim 28, the claim language relies on several items as being previously introduced (e.g. "the N linear pixel arrays" and "the N registers"), but no previous introduction has given for those respective items. Appropriate correction is required.

#### Claim Rejections - 35 USC § 102

8. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless -

- (b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.
- 9. Claims 1 4, 14 16, 23 29, and 33 50 are rejected under 35 U.S.C. 102(b) as being anticipated by West.

10. For Claim 1, West discloses, as shown in figures 4 and 5 and as stated in column 4 (lines 29 – 67) and column 5 (lines 1 – 3 and 10 – 27), a method for enhancing dynamic range of data read from an imaging sensor [see below for Examiner's interpretation of this portion of the preamble], said imaging sensor (CCD 300) comprising N linear pixel arrays (column 4, lines 3 and 4, indicates a 1340 M rows x 400 N columns CCD 300), each of the N linear arrays (400 N Columns) having M dependently controlled charge coupled pixels (1340 M Rows), each pixel charge coupled, and further being coupled to one of N registers (Horizontal Charge Transfer Register 304), the method comprising:

integrating charge in at least some pixels of the N linear pixel arrays (In at least sections 401, 402, 403,and 404; see figure 4 and column 4, lines 47 - 59);

combining charge from a first dependently controlled region (at least region 401 containing 8 rows are binned in binning row 406; see figure 4) of the N linear pixel arrays of the imaging sensor in the N registers by shifting charge from the first dependently controlled region along each of the N linear pixel arrays to each of the N registers (The binned spectra rows are reads out through horizontal register 304; see column 4, lines 66 and 67), said first dependently controlled region (401) of the N linear pixel arrays having at least one pixel line (8 rows; see column 4, lines 49 - 59, and column 5, lines 1 - 3) and said at least one pixel line of the first dependently controlled region is oriented in generally orthogonal direction to the N linear pixel arrays;

shifting charge from the N registers along a linear path (Again, West teaches that the binned spectra rows are reads out through horizontal register 304; see column 4, lines 66 and 67);

representing charge from at least a portion of the first dependently controlled region of the N linear pixel arrays, shifted out of the N registers, as a corresponding portion of N first dependently controlled region data signals (see column 5, lines 34 – 40);

combining charge from a second dependently controlled region (at least region 402 containing 8 rows are binned in binning row 406; see figure 4) of the N linear pixel arrays in the N registers by shifting charge from said at least one pixel line of the second dependently controlled region along each of the N linear pixel arrays to each of the N registers (The binned spectra rows are reads out through horizontal register 304; see column 4, lines 66 and 67), said first and second dependently controlled region (401 and 402) having at least three pixel lines, and said at least three pixel lines being oriented in generally orthogonal direction to the N linear pixel arrays;

shifting charge from the N registers along a linear path (Again, West teaches that the binned spectra rows are reads out through horizontal register 304; see column 4, lines 66 and 67); and

representing charge from at least a portion of the second dependently controlled region of the N linear pixel arrays, shifted out of the N registers, as a corresponding portion of N second dependently controlled region data signals (see column 5, lines 34 - 40).

The Examiner further notes, CCD spectroscopy of West, as stated in column 3 (lines 30 – 43), provides multiline spectroscopy wherein plural spectra are captured in a large region and binned into a smaller region.

11. As for Claim 2, West discloses, as stated in column 5 (lines 34 – 40), presenting said portion of N first dependently controlled region data signals; and presenting said portion of N

second dependently controlled region data signals (West states kinetic spectroscopy may be accomplished by capturing a single spectrum comprising multiple rows in region 302, binning such multiple row spectrum into one or more rows in region 301, and then capturing a subsequent spectrum in region 302. Spectroscopy includes displaying/presenting the captured spectra.).

12. As for Claim 3, West discloses wherein said first portion comprises N first dependently controlled region data signals (4 or 8 rows) and said second portion comprises N second dependently controlled region data signals (also 4 or 8 rows).

West states, since both the light and dark alternating area are eight rows high, the resulting arrangement is two rows of a spectrum comprising four binned rows of spectra and tow rows comprising dark charge.

- 13. As for Claim 4, West discloses, as stated in columns 4 (lines 47 67) and 5 (lines 1 4), defining the first dependently controlled region of the N linear pixel arrays of the imaging sensor (300) by designating at least one pixel line (4 or 8 lines) as belonging to the first dependently controlled region (401) of the N linear pixel arrays.
- 14. As for Claim 14, West discloses two modes for spectroscopy including kinetic and multiline. West discloses, as stated in column 5 (line 64) column 6 (line 13), programming the device with the appropriate readout mode, which alters an amount of pixel lines in a region prior to instructing said readout controller (also see column 4, line 47 column 5, line 4). Hence, West discloses wherein defining the first dependently controlled region (401) of the N linear pixel arrays of the imaging sensor is accomplished during a setup phase of a device incorporating said imaging sensor.

- 15. As for Claim 15, West discloses two modes for spectroscopy including kinetic and multiline. West discloses, as stated in column 5 (line 64) column 6 (line 13), programming the device with the appropriate readout mode, which alters an amount of pixel lines in a region prior to instructing said readout controller (also see column 4, line 47 column 5, line 4).

  Furthermore, West discloses, in column 4 (line 47) column 5 (line 4) and in column 5, lines 27 40), a four to one binning ratio can be used to compress 320 rows in region 301 into 80 rows in region 302 by an arrangement which bins according to the following algorithm: 5 to 1, 5 to 1, 4 to 1, 4 to 1, 2 to 1, 5 to 1, 5 to 1, 4 to 1, 2 to 1, repeat, etc. Hence, West discloses wherein defining the first dependently controlled region of the N linear pixel arrays of the imaging sensor is accomplished dynamically, following said integrating charge in at least some pixels of the N linear pixel arrays, and prior to a subsequent integration of charge in at least some pixels of the N linear pixel arrays.
- 16. As for Claim 16, West discloses two modes for spectroscopy including kinetic and multiline. West discloses, as stated in column 5 (line 64) column 6 (line 13), programming the device with the appropriate readout mode, which alters an amount of pixel lines in a region prior to instructing said readout controller (also see column 4, line 47 column 5, line 4).

  Furthermore, West discloses, in column 4 (line 47) column 5 (line 4) and in column 5, lines 27 40), a four to one binning ratio can be used to compress 320 rows in region 301 into 80 rows in region 302 by an arrangement which bins according to the following algorithm: 5 to 1, 5 to 1, 4 to 1, 4 to 1, 2 to 1, 5 to 1, 5 to 1, 4 to 1, 2 to 1, repeat, etc. Hence, West discloses wherein defining the first dependently controlled region of the N linear pixel arrays of the imaging sensor is accomplished dynamically, following said integrating charge in at least some pixels of the N

Art Unit: 2622

linear pixel arrays, and prior to a subsequent integration of charge in at least some pixels of the N linear pixel arrays. Hence, the Examiner considers any region with four rows to be binned as small-amplitude signals and any region with eight rows to be binned as large-amplitude signals.

Page 10

- 17. As for Claim 23, the CCD spectroscopy of West, as stated in column 3 (lines 10 18 and 30 43), provides kinetic spectroscopy wherein a single spectrum occupies multiple rows of elements that are binned to increase sensitivity and also provides multiline spectroscopy wherein plural spectra are captured in a large region and binned into a smaller region. Therefore, while not specifically shown or states, it must be that wherein a corresponding each of said portion of N first dependently controlled region data signals and each of said portion of N second dependently controlled region data signals both correspond to at least one discrete wavelength.
- 18. As for Claim 24, West discloses, as shown in figures 4 and 5 and as stated in column 4 (line 47) column 5 (line 3) and column 5 (lines 27 40), combining (in CCD region 302; see figure 5) a part of said portion of N first dependently controlled region data signals (401) with a non-corresponding part of said portion of N second dependently controlled region data signals (402); and presenting the part of said portion of N first dependently controlled region data signals and the non-corresponding part of said portion of N second dependently controlled region data signals as a plurality of data signals.

West discloses multiline spectroscopy is provided with a plurality of different spectra.

West also discloses kinetic spectroscopy is provided with a single spectrum.

19. For Claim 25, West discloses, as shown in figures 4 and 5 and as stated in column 4 (lines 29-67) and column 5 (lines 1-3 and 10-27), an imaging apparatus (300) comprising an imaging sensor (300) comprising:

N linear pixel arrays (column 4, lines 3 and 4, indicates a 1340 M rows x 400 N columns CCD 300), each of the N linear arrays (400 N Columns) having M dependently controlled charge coupled pixels (1340 M Rows);

M pixel lines (1340), said M pixel lines being oriented in generally orthogonal direction to the N linear pixel arrays;

N registers (304), wherein one pixel in each of the N linear pixel arrays being charge coupled to a respective one of the N registers;

signal converter (amplifier in figures 4 and 5 that corresponds to amplifier 104 in figure 1);

an output node coupled to said signal converter (see output line extending from said signal converter);

a memory connected to said output node (although not specifically shown; a must have feature of the CCD image sensor 300);

a readout controller coupled to said imaging sensor for controlling readout of said M dependently controlled charge coupled pixels in all the N linear pixel arrays (although not specifically shown; a must have feature of the CCD image sensor 300); and

means for instructing said readout controller (see column 6, lines 11 – 13) for combining charge from a first dependently controlled region (at least region 401 containing 8 rows are binned in binning row 406; see figure 4) of the N linear pixel arrays of the imaging sensor in the N registers by shifting charge from the first dependently controlled region along each of the N linear pixel arrays to each of the N registers (The binned spectra rows are reads out through horizontal register 304; see column 4, lines 66 and 67), said first dependently controlled region

Art Unit: 2622

Page 12

(401) of the N linear pixel arrays having at least one pixel line (8 rows; see column 4, lines 49 – 59, and column 5, lines 1 – 3) and said at least one pixel line of the first dependently controlled region is oriented in generally orthogonal direction to the N linear pixel arrays; shifting charge from the N registers along a linear path (Again, West teaches that the binned spectra rows are reads out through horizontal register 304; see column 4, lines 66 and 67); combining charge from a second dependently controlled region (at least region 402 containing 8 rows are binned in binning row 406; see figure 4) of the N linear pixel arrays in the N registers by shifting charge from said at least one pixel line of the second dependently controlled region along each of the N linear pixel arrays to each of the N registers (The binned spectra rows are reads out through horizontal register 304; see column 4, lines 66 and 67), said second dependently controlled region (403) having at least one pixel line, and said at least one pixel line of the second dependently controlled region is oriented in generally orthogonal direction to the N linear pixel arrays; shifting charge from the N registers along a linear path (Again, West teaches that the binned spectra rows are reads out through horizontal register 304; see column 4, lines 66 and 67).

The Examiner further notes, CCD spectroscopy of West, as stated in column 3 (lines 30 – 43), provides multiline spectroscopy wherein plural spectra are captured in a large region and binned into a smaller region.

- 20. As for Claim 26, West discloses wherein said memory being coupled to a display device (although not specifically shown; a must have feature of the spectroscopy system of West)
- 21. As for Claim 27, West discloses two modes for spectroscopy including kinetic and multiline. West discloses, as stated in column 5 (line 64) column 6 (line 13), programming the

Art Unit: 2622

device with the appropriate readout mode, which alters an amount of pixel lines in a region prior to instructing said readout controller (also see column 4, line 47 – column 5, line 4).

Page 13

22. For Claim 28, West discloses, as shown in figures 4 and 5 and as stated in column 4 (lines 29 – 67) and column 5 (lines 1 – 3 and 10 – 27), a computer program product, comprising a computer-readable medium (see column 6, lines 11 – 13) having stored thereon computer executable instructions for implementing a method for enhancing dynamic range of data read from an imaging sensor [see below for Examiner's interpretation of this portion of the preamble], said imaging sensor (CCD 300) comprising N linear pixel arrays (column 4, lines 3 and 4, indicates a 1340 M rows x 400 N columns CCD 300), each of the N linear arrays (400 N Columns) having M dependently controlled charge coupled pixels (1340 M Rows), each pixel charge coupled, and further being coupled to one of N registers (Horizontal Charge Transfer Register 304), said computer executable instructions comprising:

integrating charge in at least some pixels of the N linear pixel arrays (In at least sections 401, 402, 403, and 404; see figure 4 and column 4, lines 47 – 59);

combining charge from a first dependently controlled region (at least region 401 containing 8 rows are binned in binning row 406; see figure 4) of the N linear pixel arrays of the imaging sensor in the N registers by shifting charge from the first dependently controlled region along each of the N linear pixel arrays to each of the N registers (The binned spectra rows are reads out through horizontal register 304; see column 4, lines 66 and 67), said first dependently controlled region (401) of the N linear pixel arrays having at least one pixel line (8 rows; see column 4, lines 49 – 59, and column 5, lines 1 – 3) and said at least one pixel line of the first

dependently controlled region is oriented in generally orthogonal direction to the N linear pixel arrays;

shifting charge from the N registers along a linear path (Again, West teaches that the binned spectra rows are reads out through horizontal register 304; see column 4, lines 66 and 67);

representing charge from at least a portion of the first dependently controlled region of the N linear pixel arrays, shifted out of the N registers, as a corresponding portion of N first dependently controlled region data signals (As stated in column 5, lines 34 – 40, West states kinetic spectroscopy may be accomplished by capturing a single spectrum comprising multiple rows in region 302, binning such multiple row spectrum into one or more rows in region 301, and then capturing a subsequent spectrum in region 302.);

combining charge from a second dependently controlled region (at least region 402 containing 8 rows are binned in binning row 406; see figure 4) of the N linear pixel arrays in the N registers by shifting charge from said at least one pixel line of the second dependently controlled region along each of the N linear pixel arrays to each of the N registers (The binned spectra rows are reads out through horizontal register 304; see column 4, lines 66 and 67), said second dependently controlled region (403) having at least one pixel line, and said at least one pixel line of the second dependently controlled region is oriented in generally orthogonal direction to the N linear pixel arrays;

shifting charge from the N registers along a linear path (Again, West teaches that the binned spectra rows are reads out through horizontal register 304; see column 4, lines 66 and 67); and

representing charge from at least a portion of the second dependently controlled region of the N linear pixel arrays, shifted out of the N registers, as a corresponding portion of N second dependently controlled region data signals (As stated in column 5, lines 34 – 40, West states kinetic spectroscopy may be accomplished by capturing a single spectrum comprising multiple rows in region 302, binning such multiple row spectrum into one or more rows in region 301, and then capturing a subsequent spectrum in region 302.).

The Examiner further notes, CCD spectroscopy of West, as stated in column 3 (lines 30 – 43), provides multiline spectroscopy wherein plural spectra are captured in a large region and binned into a smaller region.

- 23. As for Claim 29, West discloses, as stated in columns 4 (lines 47 67) and 5 (lines 1 4), defining the first dependently controlled region of the N linear pixel arrays of the imaging sensor (300) by designating at least one pixel line (4 or 8 lines) as belonging to the first dependently controlled region (401) of the N linear pixel arrays.
- 24. For Claim 33, West discloses, as shown in figures 4 and 5 and as stated in column 4 (lines 29 67) and column 5 (lines 1 3 and 10 27), a method for reading data from an imaging sensor (300), said imaging sensor (CCD 300) comprising N linear pixel arrays (column 4, lines 3 and 4, indicates a 1340 M rows x 400 N columns CCD 300), each of the N linear arrays (400 N Columns) having M dependently controlled charge coupled pixels (1340 M Rows), each pixel charge coupled, and further being coupled to one of N registers (Horizontal Charge Transfer Register 304), the method comprising:

defining a first dependently controlled region (at least region 401 containing 8 rows are binned in binning row 406; see figure 4) of the N linear pixel arrays of the imaging sensor, said

first dependently controlled region (401) of the N linear pixel arrays having at least one pixel line (8 rows; see column 4, lines 49 - 59, and column 5, lines 1 - 3);

defining a second dependently controlled region (at least region 402 containing 8 rows are binned in binning row 406; see figure 4) of the N linear pixel arrays of the imaging sensor, said second dependently controlled region (402) having at least one pixel line, and said first and second dependently controlled regions having at least three pixel lines, and said at least three pixel lines of said first and second dependently controlled regions being oriented in generally orthogonal direction to the N linear pixel arrays (see figure 4);

defining a dark dependently controlled region (at least region 405a containing 8 rows) of the N linear pixel arrays of the imaging sensor, said dark dependently controlled region having a plurality of dependently controlled pixel lines (8 rows; see column 4, lines 47 - 57), said plurality of dependently controlled pixel lines are oriented in generally orthogonal direction to the N linear pixel arrays and said plurality of dependently controlled pixel lines are not exposed to light (see column 4, lines 31 - 34);

receiving a first image (multiline spectroscopy mode) on at least some of the pixels of the first dependently controlled region (401) of the N linear pixel arrays (see column 5, lines 10 – 40);

receiving a second image (multiline spectroscopy mode) on at least some of the pixels of the second dependently controlled region (402) of N linear pixel arrays (again see column 5, lines 10-40);

integrating charge in at least some pixels of the first dependently controlled region (401) of the N linear pixel arrays and in the at least some pixels of the second dependently controlled

region (402) of the N linear pixel arrays (in at least sections 401, 402, 403, and 404; see figure 4 and column 4, lines 47 - 59);

shifting charge from the at least some pixels of the first and second dependently controlled region (401 and 402) of the N linear pixel arrays along a linear path into said dark dependently controlled region (405a) of the N linear pixel arrays of the imaging sensor (The charges from the second region 402 must be shifted through a dark region 405a to be binned in the single row 406); and

reading out charge from said dark dependently controlled region (405a – 405d), said charge from said dark dependently controlled region having been shifted from each region (401 and 402) defined on the N linear pixel arrays of the imaging sensor (300; see column 5, lines 10 -40).

The Examiner further notes, CCD spectroscopy of West, as stated in column 3 (lines 30 – 43), provides multiline spectroscopy wherein plural spectra are captured in a large region and binned into a smaller region.

As for Claim 34, West discloses combining charge integrated in a region (301) in a 25. region of the N linear pixel arrays of the imaging sensors (300) in the N registers by shifting charge from the dark dependently controlled region (405a – 405d) along each of the N linear pixel arrays in the N registers; shifting charge from the N registers along a linear path; and representing charge from at least a portion of the region (301) of the N linear pixel arrays, shifted out of the N registers, as a corresponding portion of N data signals associated with the region (As stated in column 5, lines 34 - 40, West states kinetic spectroscopy may be accomplished by capturing a single spectrum comprising multiple rows in region 302, binning such multiple row

Art Unit: 2622

spectrum into one or more rows in region 301, and then capturing a subsequent spectrum in region 302.).

Page 18

- 26. As for Claim 35, West discloses, as stated in column 5 (lines 10 27 and 63 67) and column 6 (lines 1 6), shifting charge from the dark dependently controlled region (405a 405d) of the N linear pixel arrays of the imaging sensor (300) in the N registers; and discarding the charge shifted from the dark dependently controlled region of the N linear pixel arrays of the imaging sensor.
- 27. As for Claim 36, West discloses, as shown in figure 4, wherein the first dependently controlled region is further defined as a third region (403) and a fourth region (404) of the N linear pixel arrays of the imaging sensor.
- 28. As for Claim 37, West discloses, as stated in column 5 (lines 34 40), presenting said portion of N first dependently controlled region data signals; and presenting said portion of N second dependently controlled region data signals (West states kinetic spectroscopy may be accomplished by capturing a single spectrum comprising multiple rows in region 302, binning such multiple row spectrum into one or more rows in region 301, and then capturing a subsequent spectrum in region 302. Spectroscopy includes displaying/presenting the captured spectra.).
- 29. As for Claim 38, West discloses, as stated in column 5 (lines 34 40), presenting said portion of N third region data signals; and presenting said portion of N fourth region data signals (West states kinetic spectroscopy may be accomplished by capturing a single spectrum comprising multiple rows in region 302, binning such multiple row spectrum into one or more

rows in region 301, and then capturing a subsequent spectrum in region 302. Spectroscopy includes displaying/presenting the captured spectra.).

- 30. As for Claim 39, West discloses, as stated in column 5 (lines 10 40), wherein a sum (binning) of the pixel lines defined in said first dependently controlled region (401), said second dependently controlled region (402) and said dark dependently controlled region (405a 405d) comprises at least M pixel lines.
- 31. As for Claim 40, West discloses, as stated in column 5 (lines 20 40), wherein said plurality of pixel lines of the dark dependently controlled region (405a 405d) of the N linear pixel arrays is defined as at least M/2 pixel lines (see "binning ratio").
- 32. For Claim 41, West discloses, as shown in figures 4 and 5 and as stated in column 4 (lines 29 67) and column 5 (lines 1 3 and 10 27), a method for enhancing dynamic range of data read from an imaging sensor [see below for Examiner's interpretation of this portion of the preamble], said imaging sensor (CCD 300) comprising N linear pixel arrays (column 4, lines 3 and 4, indicates a 1340 M rows x 400 N columns CCD 300), each of the N linear arrays (400 N Columns) having M dependently controlled charge coupled pixels (1340 M Rows), each pixel charge coupled, and further being coupled to one of N registers (Horizontal Charge Transfer Register 304), the method comprising:

integrating charge in at least some pixels of a first dependently controlled region (401) of the N linear pixel arrays (In at least sections 401, 402, 403, and 404; see figure 4 and column 4, lines 47 – 59) and at least some pixels of a second dependently controlled region (402) of the N linear pixel arrays, said first dependently controlled region (at least region 401 containing 8 rows are binned in binning row 406; see figure 4) of the N linear pixel arrays of the imaging sensor,

said first dependently controlled region (401) of the N linear pixel arrays having at least one pixel line (8 rows; see column 4, lines 49 – 59, and column 5, lines 1 – 3) and said at least one pixel line of the first dependently controlled region is oriented in generally orthogonal direction to the N linear pixel arrays; and said second dependently controlled region (at least region 402 containing 8 rows are binned in binning row 406; see figure 4) of the N linear pixel arrays of the imaging sensor, said second dependently controlled region (403) having at least one pixel line, and said at least one pixel line of the second dependently controlled region is oriented in generally orthogonal direction to the N linear pixel arrays;

combining charge from a first dependently controlled region (at least region 401 containing 8 rows are binned in binning row 406; see figure 4) of the N linear pixel arrays of the imaging sensor in the N registers by shifting charge from the first dependently controlled region along each of the N linear pixel arrays to each of the N registers (The binned spectra rows are reads out through horizontal register 304; see column 4, lines 66 and 67), said first dependently controlled region (401) of the N linear pixel arrays having at least one pixel line (8 rows; see column 4, lines 49 - 59, and column 5, lines 1 - 3) and said at least one pixel line of the first dependently controlled region is oriented in generally orthogonal direction to the N linear pixel arrays;

shifting charge from the at least some pixels of the first (401) and second dependently controlled regions (402) of the N linear pixel arrays along a linear path (Again, West teaches that the binned spectra rows are reads out through horizontal register 304; see column 4, lines 66 and 67) into a dark dependently controlled region (at least region 405a containing 8 rows) of the N linear pixel arrays of the imaging sensor, said dark dependently controlled region having a

plurality of pixel lines (8 rows; see column 4, lines 47 - 57), said plurality of pixel lines are oriented in generally orthogonal direction to the N linear pixel arrays and said plurality of pixel lines are not exposed to light (see column 4, lines 31 - 34);

representing charge from at least a portion of the first dependently controlled region of the N linear pixel arrays, shifted out of the N registers, as a corresponding portion of N first dependently controlled region data signals (see column 5, lines 34 – 40);

combining charge from a second dependently controlled region (at least region 402 containing 8 rows are binned in binning row 406; see figure 4) of the N linear pixel arrays in the N registers by shifting charge from said at least one pixel line of the second dependently controlled region along each of the N linear pixel arrays to each of the N registers (The binned spectra rows are reads out through horizontal register 304; see column 4, lines 66 and 67), said second dependently controlled region (403) having at least one pixel line, and said at least one pixel line of the second dependently controlled region is oriented in generally orthogonal direction to the N linear pixel arrays;

shifting charge from the N registers along a linear path (Again, West teaches that the binned spectra rows are reads out through horizontal register 304; see column 4, lines 66 and 67);

representing charge from at least a portion of the second dependently controlled region of the N linear pixel arrays, shifted out of the N registers, as a corresponding portion of N second dependently controlled region data signals (see column 5, lines 34 – 40);

and clearing charge from the dark dependently controlled region of the N linear pixel arrays of the imaging sensor (column 6, lines 1-6).

Art Unit: 2622

The Examiner further notes, CCD spectroscopy of West, as stated in column 3 (lines 30 – 43), provides multiline spectroscopy wherein plural spectra are captured in a large region and binned into a smaller region.

- 33. As for Claim 42, West discloses, as stated in column 5 (lines 34 40), presenting said portion of N first dependently controlled region data signals; and presenting said portion of N second dependently controlled region data signals (West states kinetic spectroscopy may be accomplished by capturing a single spectrum comprising multiple rows in region 302, binning such multiple row spectrum into one or more rows in region 301, and then capturing a subsequent spectrum in region 302. Spectroscopy includes displaying/presenting the captured spectra.).
- 34. As for Claim 43, West discloses wherein said first portion comprises N first dependently controlled region data signals (4 or 8 rows) and said second portion comprises N second dependently controlled region data signals (also 4 or 8 rows).
- West states, since both the light and dark alternating area are eight rows high, the resulting arrangement is two rows of a spectrum comprising four binned rows of spectra and tow rows comprising dark charge.
- As for Claim 44, West discloses integrating charge in at least some pixels of a first dependently controlled region (401) of the N linear pixel arrays (In at least sections 401, 402, 403, and 404; see figure 4 and column 4, lines 47 59) and at least some pixels of a second dependently controlled region (402) of the N linear pixel arrays, said first dependently controlled region (at least region 401 containing 8 rows are binned in binning row 406; see figure 4) of the N linear pixel arrays of the imaging sensor, said first dependently controlled region (401) of the

Art Unit: 2622

N linear pixel arrays having at least one pixel line (8 rows; see column 4, lines 49 - 59, and column 5, lines 1 - 3) and said at least one pixel line of the first dependently controlled region is oriented in generally orthogonal direction to the N linear pixel arrays; and said second dependently controlled region (at least region 402 containing 8 rows are binned in binning row 406; see figure 4) of the N linear pixel arrays of the imaging sensor, said second dependently controlled region (403) having at least one pixel line, and said at least one pixel line of the second dependently controlled region is oriented in generally orthogonal direction to the N linear pixel arrays.

Page 23

- 37. As for Claim 45, West discloses, as stated in column 6 (lines 1-6), wherein clearing charge from the dark dependently controlled region of the N linear pixel arrays further comprises: shifting charge from the dark dependently controlled region of the N linear pixel arrays of the imaging sensor in the N registers; and discarding the charge shifted from the dark dependently controlled region of the N linear pixel arrays of the imaging sensor.
- 38. As for Claim 46, West discloses, as stated in column 5 (lines 10 40), wherein a sum (binning) of the pixel lines defined in said first dependently controlled region (401), said second dependently controlled region (402) and said dark dependently controlled region (405a 405d) comprises at least M pixel lines.
- 39. As for Claim 47, West discloses, as stated in column 5 (lines 20 40), wherein said plurality of pixel lines of the dark dependently controlled region (405a 405d) of the N linear pixel arrays is defined as at least M/2 pixel lines (see "binning ratio").
- 40. As for Claim 48, West discloses multiline spectroscopy including a plurality of spectra. Furthermore, West discloses, in column 5 (lines 14 9) and column 5 (line 56) column 6 (line

- 6), wherein said first dependently controlled region (401) of the N linear pixel arrays having a first image (first spectra) projected thereon, and said second dependently controlled region (402) of the N linear pixel arrays having a second image (second spectra) projected thereon.
- 41. As for Claim 49, West discloses multiline spectroscopy including a plurality of spectra. Furthermore, West discloses, in column 5 (lines 14 9) and column 5 (line 56) column 6 (line 6), wherein said first dependently controlled region (401) of the N linear pixel arrays being exposed to a first light source (first spectra), and said second dependently controlled region (402) of the N linear pixel arrays being exposed to a second light source (second spectra)
- 42. As for Claim 50, West discloses integrating charge in at least some pixels of a one other region (403 404) of the N linear pixel arrays (In at least sections 401, 402, 403, and 404; see figure 4 and column 4, lines 47 59), said other region (403 404) of the N linear pixel arrays having at least one pixel line (8 rows; see column 4, lines 49 59, and column 5, lines 1 3) and said at least one pixel line of the other region is oriented in generally orthogonal direction to the N linear pixel arrays;

shifting charge from the at least some pixels of the other region (403 – 404) of the N linear pixel arrays along a linear path (Again, West teaches that the binned spectra rows are reads out through horizontal register 304; see column 4, lines 66 and 67) into a dark dependently controlled region (at least region 405a containing 8 rows) of the N linear pixel arrays of the imaging sensor,

for each of the at least other region (403 or 404), combining charge in one of the at least one other region (at least region 402 containing 8 rows are binned in binning row 406; see figure 4) of the N linear pixel arrays in the N registers by shifting charge from said at least one pixel

Application/Control Number: 10/612,125 Page 25

Art Unit: 2622

line of the dark dependently controlled region along each of the N linear pixel arrays to each of the N registers (The binned spectra rows are reads out through horizontal register 304; see column 4, lines 66 and 67), and

shifting charge from the N registers along a linear path (Again, West teaches that the binned spectra rows are reads out through horizontal register 304; see column 4, lines 66 and 67).

# Allowable Subject Matter

- 43. Claims 5 13, 17 22, and 30 32 are objected to as being dependent upon a rejected base claim, but would be allowable if rewritten in independent form including all of the limitations of the base claim and any intervening claims.
- 44. The following is a statement of reasons for the indication of allowable subject matter:

As for Claims 5 - 13 and 30 - 32, while the closest prior art discloses multiline spectroscopy or kinetic spectroscopy utilizing a CCD image sensor and pixel line binning for binning a plurality of pixel lines from a plurality of different regions on the CCD image sensor to increase spectrum/spectra sensitivity;

The closest prior art does not teach or fairly suggest determining/adjusting an amount of pixel lines belonging to at least one of said plurality of different regions, wherein the amount the pixel lines relates to the level of improvement in dynamic range or relates to the comparison of a target signal level.

As for Claims 17 – 22, while the closest prior art discloses two modes for spectroscopy including kinetic and multiline, programming the spectroscopy device with the appropriate readout mode, which alters an amount of pixel lines in a region prior to instructing said readout

mode, wherein the readout mode alters the readout binning mode such that a four to one binning ratio can be used to compress a large number of rows in into a smaller number of rows, wherein the large number rows may be divided into separate regions of rows having corresponding large and small amplitude signals;

The closest prior art does not teach or fairly suggest re-scaling one of said small-amplitude signals from said first dependently controlled region and said large-amplitude signals from said second dependently controlled region or determining a relationship between said small-amplitude signals of said first channel from said first dependently controlled region, and said large-amplitude signals of said second channel from said second dependently controlled region.

## Conclusion

45. THIS ACTION IS MADE FINAL. Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire THREE MONTHS from the mailing date of this action. In the event a first reply is filed within TWO MONTHS of the mailing date of this final action and the advisory action is not mailed until after the end of the THREE-MONTH shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event, however, will the statutory period for reply expire later than SIX MONTHS from the mailing date of this final action.

Application/Control Number: 10/612,125 Page 27

Art Unit: 2622

46. Any inquiry concerning this communication or earlier communications from the Examiner should be directed to Justin P Misleh whose telephone number is 571.272.7313. The Examiner can normally be reached on Monday through Friday from 8:00 AM to 5:00 PM.

If attempts to reach the Examiner by telephone are unsuccessful, the Examiner's supervisor, David L Ometz can be reached on 571.272.7593. The fax phone number for the organization where this application or proceeding is assigned is 571.273.3000.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

JPM June 17, 2006

SUPERVISORY PATENT EXAMINER